CLAIM AMENDMENTS

(Currently amended) Procedure for the A method of 1 scheduling of a service resource shared among several information 2 packet flows that generate respective associated queues, 3 said flows including synchronous flows 4 $(i = 1, 2, ..., N_s)$ that require a guaranteed minimum service rate 5 (r_i) and asynchronous flows $(i = 1, 2, ..., N_a)$ that use the service 6 capacity of said resource that is left unused by the synchronous 7 flows, the procedure method making use of a server (10) and 8 comprising the following operations steps of: - makes causing said server (10) visit .the respective 10 queues associated to said flows (i, j) in successive cycles on the 11 basis of the target rotation time value (TTRT), which identifies 12 the time necessary for the server (10) to complete a visit cycle on 13 said respective queues: [[,]] 1.4 - associates associating each synchronous flow (i) with 15 a respective synchronous capacity value (H,) indicating the maximum 16 period of time for which the respective synchronous flow can be 17 serviced before the server moves on, 18 -associates associating each asynchronous flow (j) with 19 a first respective delay value (L;) that identifies the value that 20 must be made up for the respective queue to have the right to be 21 serviced, and a second respective value (last_visit_time) that 22

39

40

41

indicates the instant in which the server (10) visited the 23 respective queue in the previous cycle, determining for said 24 respective queue, the time that has elapsed since the server's 25 previous visit; [[,]] 26 -services servicing each queue associated to a 27 synchronous flow (i) for a maximum service time relative to said 28 respective value of synchronous capacity (Hi), [[and]] 29 - services servicing each queue associated to an asynchronous 30 flow (j) only if the server's visit (10) occurs before the expected 31 instant, said advance being determined as the difference between 32 said target rotation time value (TTRT) and the, time that has 33 elapsed since the server's (10) previous visit and the accumulated 34 delay, so that [[;]] if positive, this difference, defines the 35 maximum service time for each asynchronous queue; [[,]] 36 37 The procedure also includes the operation that defines

for the queue associated to the i-th synchronous flow by

- i) the expressions

satisfying:

$$\sum_{i=1}^{N_s} H_i + \tau_{\max} \leq TTRT$$

$$TTRT \geq \frac{\tau_{\max}}{1 - \sum_{i=1}^{N_s} r_i / C}$$

defining said respective synchronous capacity value (H,)

ii) as well as at least one of the following expressions

$$H_{i} = \frac{r_{i} \cdot TTRT}{C} \text{ and}$$

$$H_{i} = \frac{(N_{A} + \alpha) \cdot r_{i}/C}{N_{A} + 1 - \sum_{h=1}^{N_{S}} r_{h}/C} \cdot TTRT$$

43 - H_i is said respective synchronous capacity

- value (H_i)
- for the queue associated to the i-th synchronous flow,
- the summations are extended to all the synchronous
- flows, equal to NS,
- NA is the number of said asynchronous flows,
- T_{max} is the duration of the longest packet service by
- said shared service resource,
- TTRT is said target rotation time value,
- 52 C is the service capacity of said shared service
- resource,
- r_i is the minimum service rate required by the i-th
- synchronous flow, with

$$\sum_{h=1}^{N_s} r_h / C < 1$$

- 57 , and
- α is a parameter that gives $\sum_{h=1}^{N_s} r_h/C \le 1-\alpha$

Ţ;

- 2. (Currently amended) Procedure as per claim 1 1 characterized by the fact that The method defined in claim 1 2 wherein during each of said successive cycles, said server (10) 3 performs a double scan on all the queues associated: to said synchronous flows $(j = 1, 2, ..., N_a)$. 5 3. . 1 (Currently amended) Procedure as per claim 2, **}**2 characterised by the fact that it includes The method defined in claim 2 which comprises the following operations: 3 - associates associating to each synchronous flow (i) a further value (Δi) indicating the amount of service time that is 5 available to the respective flow, 6 [[-]] during a major cycle of the said double scan, serving it services each queue associated to a synchronous flow 8 (i) for a period of time equal to the maximum said further value (Δ_i) , and during a minor cycle of said double scan it services 10 only one packet of each queue associated to a synchronous flow (i), 11
- 4. (Currently amended) Procedure as per claim 3,

 characterised by the fact that it The method defined in claim 3

 which includes the operation of incrementing said further value

provided that said further value (Δ_i) is strictly positive.

- 4

- (Δ_i) by said respective value of the synchronous capacity (H_i) when
- the queue is visited during the major cycle of said double scan. 5
- (Currently amended) Procedure as per claim 3 or claim 5. 1 4, characterised by the fact that it The method defined in claim 3 2 which includes the operation of decrementing said further value 3 (Δ_i) of the transmission time by each packet serviced.
- 6. (Currently amended) Procedure as per any of the claims 1 3 to 5, characterized by the fact that The method defined in claim 2 3 wherein the service of each queue associated to a synchronous flow (i) during the major cycle of said double scan ends when one of the following conditions occurs: 5
- [[-]] the queue is empty, 6
- [[-]] the time available, represented by said further 7 · 8 value (Δ_i) , is not sufficient to service the packet at the front of the queue. 9
- 7. (Currently amended) Procedure as per claim 6, 1 characterized by the fact that it The method defined in claim 6 2 which includes the operation of resetting said further value (Δ_i) 3 when the respective queue is empty.

(i) has been visited,

7

- 8. (Currently amended) Procedure as per any of the claims

 2 3 to 7, characterized by the fact that it The method defined in

 3 claim 3 which includes the operation of decrementing the service

 4 time of said further value (Δ_i) in the presence of a service given

 5 during the minor cycle of said double scan.
- 9. (Currently amended) Procedure as per any of the

 claims 3 to 8, characterized by the fact that The method defined in

 claim 3 wherein during said double scan of all the queues

 associated to said synchronous flows (i), said minor cycle ends

 when one of the following conditions is satisfied:

 [[-]] the last queue associated to a synchronous flow
- [[-]] a period of time not less that the sum of the capacities (Hi) of all the queues associated to said synchronous flows (i) has elapsed since the beginning of said major cycle of said double scan.
- 10. (Currently amended) Procedure as per any of the

 claims 3 to 9, characterized by the fact that it The method defined

 in claim 9 which includes the operation of initialising said

 further value (Δ_i) to zero.

- 7 -

- 11. (Currently amended) Procedure as per any of the

 2 previous claims, characterized by the fact that The method defined

 3 in claim 10 wherein in the case that said difference is negative,

 4 each said queue associated to an asynchronous flow (j) is not

 5 serviced and the value of said difference is accumulated with said

 6 delay (L_i).
- 12. (Currently amended) Procedure as per any of the

 claims 1 to 11, characterized by the fact that The method defined

 in claim 11 wherein the service servicing of a queue associated to

 an asynchronous flow (j) ends when one of the following conditions

 is satisfied:
 - [[-]] the queue is empty;
- [[-]] the time available is not sufficient to service
 the packet at the front of the queue.
- 1 13. (Currently amended) Procedure as per any of the

 claims 1 to 12, characterized by the fact that The method defined

 in claim 12 wherein said first respective value (L_j) and said

 second respective value (last_visit_time) are respectively

 initialised to zero and to the moment of startup of the current

 cycle when the flow is activated.

29

ż

14. (Currently amended) System A system for the 7 scheduling of a service resource shared among several a plurality 8 of information packet[[s]] flows that generate respective 9 associated queues, said . Said flows include including synchronous 10 flows (i = 1, 2, ..., N_s) that require a guaranteed minimum service 11 rate and asynchronous flows $(j = 1, 2, ..., N_s)$ destined to use the 12 service capacity of said resource left unused by the synchronous 13 flows, and comprising. The system also includes a server (10) able 14 to visit the respective queues associated to said flows (i, j) in 15 successive cycles, and which is configured to perform the following 16 operations: 17 [[-]] determine a target rotation time value (TTRT) that 18 identifies the time necessary for the server (10) to complete a 19 visiting cycle of said respective queues, 20 [[-]] associate to each synchronous flow (i) a 21 respective synchronous capacity value (H_i) indicating the maximum 22 23 amount of time for which a synchronous flow can be serviced before Ź4 moving on to the next, 2**5** [[-]] associate to each asynchronous flow (j) a first respective delay value (L;) that identifies the delay that must be 26 made up for the respective queue to have the right to be serviced, 27

- 9 -

and a second respective value (last visit time) that indicates the

instant in which in the previous cycle the server (10) visited the

respective queue, determining for said respective queue, the time
that has elapsed since the server's (10) previous visit,

[[-]] service each queue associated to a synchronous flow

(i) for a maximum period of time relating to said respective synchronous capacity value (H_i), and

[[-]] service each queue associated to an asynchronous flow (j) only if the server's visit (10) occurs before the expected instant, said advance being determined as the difference between said target rotation time (TTRT) and the time that has elapsed since the server's (10) previous visit and the accumulated delay; if positive, this difference defines the maximum service time for each said asynchronous queue.

the system [[is]] <u>being</u> configured to define said respective synchronous capacity value (Hi) for the queue associated to the i-th synchronous flow so that the following are satisfied:

i) the expressions

$$\sum_{i=1}^{N_s} H_i + \tau_{\max} \leq TTRT$$

$$TTRT \ge \frac{\tau_{\max}}{1 - \sum_{k=1}^{N_s} r_k / C}$$

- ii) as well as at least one of the following expressions

$$H_i = \frac{r_i \cdot TTRT}{C}$$
 and

49

$$H_i = \frac{(N_A + \alpha) \cdot r_i / C}{N_A + 1 - \sum_{h=1}^{N_S} r_h / C} \cdot TTRT$$

50 where:

- 51 H_i is the said respective synchronous capacity value
- 52 (Hi) for the queue associated to the i-th synchronous flow,
- the summations are extended to all the synchronous
- flows, equal to N_s,
- [[-]]N_A is the number of said asynchronous flows,
- [[-]] T_{max} is the service duration of the longest packet by
- said shared service resource,
- [[-]]TTRT is said target rotation time value,
- [[-]] C is the service capacity of said shared service
- 60 resource,

63

- [[-]] r_i is the minimum service rate requested by the
- 62 i-th synchronous flow, with

$$\sum_{h=1}^{N_s} r_h/C < 1$$
 and $\sum_{h=1}^{N_s} r_h/C \le 1-lpha$

- α is a parameter that gives

11

```
15.
1
                     (Currently amended) System as per claim 14,
     characterized by the fact that The system of claim 14 wherein
2
     during each of the said successive cycles, said server (10)
3
     performs a double scan on all the queues associated to said
     synchronous flow (i = 1, 2, ..., N_s) and then visits the queues
5
     associated to said asynchronous flows (j = 1, 2, ..., N_k).
6
                    (Currently amended) System as per claim 15,
1
     characterized by the fact that The system of claim 15 wherein:
2
               - a further value (\Delta i) indicating the amount of service
3
     time available to the respective flow, is associated to each
4
     synchronous flow (i),
5
               - during a major cycle of said double scan, each queue
     associated to a synchronous flow (i) is serviced for a period of
7
    time equal to the maximum further value (\Delta_i), and
8
               - during a minor cycle of said double scan the system
```

17. (Currently amended) System as per claim 16,

characterized by the fact that The system of claim 16 wherein said

further value (Δ_i) is incremented by said respective synchronous

services only one packet of each queue associated to a synchronised

flow (i), provided said further value (Δ_i) is strictly positive.

- 12 -

- 4 capacity value (H_i) when the queue is visited during the major
- 5 double scan cycle.
- 18. (Currently amended) System as per claim 16 or claim 17, characterized by the fact that The system of claim 17 wherein said further value (Δ_i) is decremented by the transmission time of each packet serviced.
- 19. (Currently amended) System as per any of the claims
 2 16 to 18, characterized by the fact that the system is The system
 3 of claim 18 which is configured so that the service of each queue
 4 associated to a synchronous flow (i) during the major cycle of said
 5 double scan ends when one of the following conditions occurs:
 - the queue is empty,
- the time available, represented by said further value (Δ_i) , is not sufficient to serve the packet at the front of the queue.
- 20. (Currently amended) System as per claim 19,
 characterized by the fact that The system of claim 19 wherein said
 further value (Δ_i) is reset when the respective queue is empty.

- 3 wherein in the presence of a service given during the minor cycle
- of said double scan, said further value (Δ_i) is decremented by the
- 5 amount of service time.
- 22. (Currently amended) System as per any of the claims
- 2 16 to 21, characterized by the fact that The system of claim 21
- 3 wherein during said double scan on all the queues associated to
- said synchronous flows (i), said minor cycle ends when one of the
- following conditions is satisfied:
- the last queue associated to a synchronous flow (i) has
- peen visited,
- a period of time not less than the sum of the
- 9 capacities (Hi) of all the queues associated to said synchronous
- 10 flows (i) has elapsed since the beginning of said major cycle of
- 11 said double scan.
- 1 23. (Currently amended) System as per any of the
- 2 previous claims 16 to 22, characterized by the fact that The system
- of claim 22 wherein said further value (Δ_i) is initialised to zero.
- 24. (Currently amended) System as per any of the previous
- 2 claims 16 to 23, characterized by the fact that The system of claim
- 3 <u>23 wherein</u> if said difference is negative, each said queue

- associated to an asynchronous flow (j) is not services and the
- value of said difference is accumulated with said delay (L_i).
- 6 25. (Currently amended) System as per any of the claims
- 14 to 24, characterized by the fact that The system of claim 24
- 8 wherein the service of a queue associated to an asynchronous flow
- 9 (j) ends when one of the following conditions is satisfied:
- the queue is empty,
- the time available is not sufficient to transmit the
- packet that is at the front of the queue.
- 1 26. (Currently amended) System as per any of the claims
- 2 14 to 25, characterized by the fact that The system of claim 25
- wherein said first respective value (L,) and said second respective
- value (last_visit_time) are respectively initialised to zero and to
- the moment of startup of the current cycle when the flow is
- 6 activated.